## Span F500S

Powered Sit-to-Stand Patient Lift



- High Capacity: 500 lb (228 kg) safe working load.
- Care Flexibility: Underbed clearance allows use with most low beds.
- Safe and Reliable: Redundant controls; overload protection; emergency lowering; 3-year frame warranty.
- **Easy operation:** Simple charging; audible/visual indicators; locking rear casters.























better science. better care.





## F500S Sit-To-Stand Patient Lift

An essential tool for safe, efficient patient transfers between bed, chair and commode. Compact and easy to maneuver in a variety of settings, the F500S delivers a winning combination of safety, simplicity, and value.





LCD battery level display; audible low-battery indicator



2-button pendant with LED indicator



Underbed clearance, allows use with most low beds



Contoured knee pad with 3 height settings

- **SPECIFICATIONS** 500 lb / 228 kg Weight Capacity External base width (closed) 24.9" Internal leg width (opened) 33.9" 40" Upright mast height Overall base length 37.5" Base Height 4.9" 38" Min. lifting height with spreader bar Max. lifting height with spreader bar 60.5" Knee pad length extension range 4.5" Max. boom width 17.7" Net Weight 111 lb / 50.3 kg 119 lb / 53.9 kg **Shipping Weight**
- **Easy base width adjustment** with locked position; accommodates chairs and commodes.
- Wide non-slip footplate provides stable base for transfer.
- Redundant operation via control unit, allowing use if pendant is lost or damaged.
- Overload protection with visual/audible alert, halts lifting when capacity is exceeded.
- Manual emergency lowering for added safety.
- Quick-release battery can be charged via charging cradle (optional), or via plug-in charger (included) for charging in place.
- Backlit LCD display during operation for ease of viewing.
- Simple, fast assembly using tools provided.
- Certified to: ISO 10535; IEC/EN/ANSI/AAMI/CAN/CSA-C22.2 60601-1, 60101-1-2, and 60601-1-11; SGS Mark for Safety.

Item #	Description
F500S	Sit-To-Stand Patient Lift
Warranty:	3 years (frame and spreader bar);
	2 years (electronics); 1 year (battery)

## Part of Span's line of Safe Patient Handling and Mobility solutions, including:

F500P Full Body Patient Lift

F450T Standing Transfer Aid



Fixed Lithium-ion

Overhead Lifts



Portable Lithium-ion



Floor Lifts





